

## DESCRIPTION

The PSP 40-400 Chemical PVC Blue is a chemical resistant PVC glove. Due to the special PVC formula, it offers triple protection against oil compared to regular PVC gloves. This glove is "Triple Dipped" for excellent oil, alkalis and acid resistance. The rough (Sandy) finish provides good grip in all conditions.

This glove is also extremely flexible at low temperatures. The 15 G cotton liner on the inside provides a nice and cool feeling and is treated antibacterial and therefore odor-free.


Article PSP 40-400 has been tested and certified in accordance with the European Regulation (EU) 2016/425 and the EN-standards EN ISO 21420:2020 / EN388:2016 / EN ISO 374-1 type A et EN ISO 374-5.

## CHARACTERISTICS


- ▲ PVC with a special formula; extremely good protection against oil
- ▲ Triple Dipped
- ▲ Extremely flexible PVC
- ▲ Good grip in wet and oily environments
- ▲ High wearing comfort
- ▲ Antibacterial treatment on the inside
- ▲ Protects against oils, greases, alkalis, acids, solvents and several chemicals.
- ▲ Certification according to: EN ISO 21420:2020 / EN388:2016 / EN ISO 374-1 type A et EN ISO 374-5.



## CERTIFICATIONS


  
CAT III

EN 388:2016  
+A1:2018


  
4121X

Abrasion resistance = 4  
Cut resistance = 1  
Tear resistance = 2  
Puncture resistance = 1  
Cut ISO 13997 = X

EN ISO 374-1:2016  
+A1:2018/Type A

  
AJKLMNOPT

EN ISO 374-5: 2016



## APPLICATIONS

(Petro)chemistry | Pharmacy | Automotive | Oil / offshore  
Fisheries | Food industry | Construction



## PRODUCT INFORMATION

<b>Material</b>	Liner: Cotton Coating: PVC (triple dipped) with sandy finish all around the hand
<b>Color</b>	Blue
<b>Inner lining</b>	Cotton
<b>Length (mm)</b>	300
<b>Cuff</b>	Gauntlet style

## ORDER DETAILS

Size	Item number	Packing unit
07 / S	2.04.40.400.07	6 x 12 (72 pairs)
08 / M	2.04.40.400.08	6 x 12 (72 pairs)
09 / L	2.04.40.400.09	6 x 12 (72 pairs)
10 / XL	2.04.40.400.10	6 x 12 (72 pairs)
11 / XXL	2.04.40.400.11	6 x 12 (72 pairs)
12 / 3XL	2.04.40.400.12	6 x 12 (72 pairs)

\*\* Liquid protection: Note! The degree of protection depends on the coating used.  
Cut ISO 13997: The letter A to F indicates the cut resistance according to ISO 13997. X = control not performed or not applicable

