



DESCRIPTION





The PSP 40-436 Chemical PVC Blue is a chemical resistant PVC glove measuring 36 cm. Due to its special PVC formula, it offers triple protection against oil compared to regular PVC gloves. This glove is "Triple Dipped" for excellent oil, alkalis and acid resistance. The rough (Sandy) finish ensures a good grip in all conditions. Even at low temperatures, this glove is extremely flexible. The 15 G cotton liner on the inside provides a nice and cool feeling and is antibacterial treated and therefore odor free.

Article PSP 40-436 has been tested and certified in accordance with the European Regulation (EU) 2016/425 and EN standards EN ISO 21420:2020 / EN388:2016 / EN ISO 374-1 type A and EN ISO 374-5.

CHARACTERISTICS

- ▲ PVC with a special formula; extremely good protection against oil
- ▲ Triple Dipped
- ▲ Extremely flexible PVC
- ▲ Good grip in wet and oily environments
- ▲ High wearing comfort
- ▲ Antibacterial treatment on the inside
- ▲ Protects against oils, greases, alkalis, acids, solvents and several chemicals.
- ▲ Inspections in accordance with: EN ISO 21420:2020 / EN388:2016 / EN ISO 374-1 type A and EN ISO 374-5.

CERTIFICATIONS

 CAT III	EN 388:2016 +A1:2018  4121X Abrasion resistance = 4 Cut resistance = 1 Tear resistance = 2 Puncture resistance = 1 Cut ISO 13997 = X	EN ISO 374-1:2016 +A1:2018/Type A  AJKLMNOPT	EN ISO 374-5: 2016 
---	---	--	--

APPLICATIONS

(Petro)chemistry | Pharmacy | Automotive | Oil / offshore
Fisheries | Food industry | Construction



PRODUCT INFORMATION

Material	Liner: Cotton Coating: PVC (triple dipped) with sandy finish all around the hand
Color	Blue
Inner lining	Cotton
Length (mm)	360 (size 10, depending on size)
Cuff	Gauntlet style

ORDER DETAILS

Size	Item number	Packing unit
07 / S	2.04.40.436.07	6 x 12 (72 pair)
08 / M	2.04.40.436.08	6 x 12 (72 pair)
09 / L	2.04.40.436.09	6 x 12 (72 pair)
10 / XL	2.04.40.436.10	6 x 12 (72 pair)
11 / XXL	2.04.40.436.11	6 x 12 (72 pair)
12 / 3XL	2.04.40.436.12	6 x 12 (72 pair)

** Liquid protection: Note! The degree of protection depends on the coating used.
Cut ISO 13997: The letter A to F indicates the cut resistance according to ISO 13997. X = control not performed or not applicable

