

Product data sheet for uvex profaviton



Manufacturer address

UVEX SAFETY Gloves GmbH & Co. KG
Elso-Klöver-Str. 6
D-21337 Lüneburg
uvex-safety.de

This glove is made from butyl and has a Viton® outer layer that is around 0.2 mm thick. The overall thickness of the glove is around 0.6 mm. The Viton® layer is resistant to aliphatic and aromatic hydrocarbons (e.g. hexane, benzene, toluene, xylene and others), halogenated hydrocarbons (e.g. trichloroethylene, perchloroethylene, dichloromethane and others), organic and inorganic acids (diluted to concentrated), as well as saturated saline solutions.

Features

- Highly durable

| | |
|--|---|
| Material number | 60957 |
| Sizes | 8,9,10,11 |
| Standard | EN ISO 21420:2020, EN 388:2016 + A1:2018, EN ISO 374-1:2016 + A1:2018 |
| Test chemicals | Methanol (A), Toluene (F), Sodium hydroxide 40% (K), Sulphuric acid 96% (L), Nitric acid 65% (M), Acetic acid 99% (N) |
| Performance classes in accordance with EN 388 | 2 1 2 0 A |
| Outer material | No lining |
| Coating | Bromobutyl, Viton® |
| Coating surface area | Fully coated |
| Type | With rolled edge |
| Colour | Black |