

## **Product datasheet**

## uvex 2 BOA® 6506 1-3

Safety boot DIN EN ISO 20345:2022 S3L FO SC SR Sizes: 35 - 52 | Width: 10, 11, 12











## **AREA OF APPLICATION**

Medium applications usually alternate between indoor and outdoor areas, meaning that the demands on the robustness of the outsole of a safety shoe are much higher.

## **OUTSOLE**

**Dual density Polyurethan** 



- Shock-absorbing PU midsole
- Antistatic
- Short-term heat resistant up to 120°C
- Excellent slip resistance (SR)
- Oil and fuel resistant (FO)
- Free of silicones, plasticisers and other substances that interfere with wetting agents





FEATURES	
Upper material	Leather
	Water repellent (WPA)
Lining material	Textile Distance-Mesh lining for comfortable foot climate
Fastening	BOA® Fit System
Heel basket	Foamed PU heel basket for additional stability in the shoe
Reflecting elements	For increased visibility even in dark working
	environments
Comfort	Soft padding on collar
	Sizes 35-40 have been produced using a women's last
	Dust tongue
Insock	Removable comfortable insock
PROTECTIVE FEATUR	RES
Toe cap	Metal-free toe cap
Anti-penetration	Metal-free, textile anti-penetration
Scuffcap	Out of PU for additional protection of the upper material (SC)
CERTIFICATES	
uvex medicare+	Certified for orthopaedic insocks and shoe adjustments according to the description in <b>DGUV 112-191</b>
ESD	<ul> <li>Protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1</li> </ul>
SUSTAINABILITY	
Recycled/sustainable materials	Removable insock made wholly or partly from recycled materials
	Free from harmful substances in accordance with the uvex restricted substances list
<b>ACCESORIES/ SPARE</b>	PARTS
Replacement insock	• 9534 7-0
tune-up insock	• low 95281
	medium 95282
	high 95283