

SAFETY FOOTWEAR

24.02.2022 SBU-F-PGM-PM

Product Datasheet uvex 2 MACSOLE® 6523 1-4 S3 HI HRO SRC





UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth

General features	 Light and flexible S3 safety boots
	Water-repellent, full-grain smooth leather
	 Foamed polyurethane scuffcap helps increase
	product life of upper
Protection features	 meets the ESD specification with volume resistance under 35 megaohms Metal-free uvex xenova® protective toe cap – compact design, anatomical shape, good lateral
	stability and no thermal conductivity
	ultra-lightweight, double-layer sole made from optimal shock-absorbing polyurethane midsole and uvex MACSOLE® rubber outsole with excellent anti-slip properties
	 HI marking for heat-insulating substructure (tested in accordance with standard at +150°C)
	 HRO marking for heat-resistant substructure for brief exposure up to +300°C
	 secure grip when climbing on ladders due to the stabilising arch support
	 penetration-resistant, non-metallic midsole in
	accordance with current safety standards, does not restrict flexibility of the shoe
Comfort features	Outstanding wearer comfort regults from a newly
Comfort features	 Outstanding wearer comfort results from a newly developed last and climate-optimised, breathable materials
	 Virtually seamless design to eliminate pressure

Rev. St. 1 Datum: 12.05.2014 Seite 1 von 2

	Removable comfort insole, antistatic, with moisture
	control system and additional shock absorption in the heel and at the front of the foot
	Soft padded collar and tongue
Outsole	 Multilayer shock absorption system comprising PU mid sole, highly slip resistance rubber outsole from uvex MACSOLE® and comfortable insole, shock absorption in the front and heel Increased low-temperature flexibility of uvex MACSOLE® rubber sole Rugged, self-cleaning sole ridges ensures maximum grip for demanding applications on uneven or dirty floors (SRC labelling). withstands brief exposure to heat of approx. +300°C
Certificates	 Certified with uvex medicare for individual, orthopaedic inlay soles and individual adjustments of the sole unit such as overall increase, inside and outside increase and other solutions.
Areas of application	Medium applications
Technical data	Artno. 6523 1 2 3 4 Width 10 11 12 14 Standard EN ISO 20345:2011 S3 HI HRO SRC Size 35 – 52
Accessories	 uvex 1/2 comfortable climatic insole (article no.: 9534.7-9 + .0) Provides the foot with exceptional, full-surface shock absorption and ensures comfort in high-strain zones Ultra-breathable and moisture-absorbing materials Shock absorption zones that assist natural movement Non-irritating, comfortable surface structure Laces Black (article no.: 9599.9 11)
	Elastic laces (article no.: 9591.100)

Rev. St. 1 Datum: 12.05.2014 Seite 2 von 2