

SAFETY FOOTWEAR

24.02.2022 PGM-F-MA

Product Datasheet uvex 2 MACSOLE® 6530 3 S3 HI CI HRO SRC





UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth

General features	 Light and flexible S3 safety boots Water-repellent, full-grain smooth leather Foamed polyurethane scuffcap helps increase product life of upper
Protection features	 meets the ESD specification with volume resistance under 35 megaohms Metal-free uvex xenova® protective toe cap — compact design, anatomical shape, good lateral stability and no thermal conductivity ultra-lightweight, double-layer sole made from optimal shock-absorbing polyurethane midsole and uvex MACSOLE® rubber outsole with excellent anti-slip properties HI marking for heat-insulating substructure (tested in accordance with standard at +150°C) HRO marking for heat-resistant substructure for brief exposure up to +300°C secure grip when climbing on ladders due to the stabilising arch support penetration-resistant, non-metallic midsole in accordance with current safety standards, does not restrict flexibility of the shoe
Comfort features	 Outstanding wearer comfort results from a newly developed last and climate-optimised, breathable materials Virtually seamless design to eliminate pressure

Rev. St. 1 Datum: 12.05.2014 Seite 1 von 2

	Removable comfort insole, antistatic, with moisture
	control system and additional shock absorption in the
	heel and at the front of the foot
	Soft padded collar and tongue
	Warm lining with optimum breathability
Outsole	Multilayer shock absorption system comprising PU
	mid sole, highly slip resistance rubber outsole from
	uvex MACSOLE® and comfortable insole, shock
	absorption in the front and heel
	Increased low-temperature flexibility of uvex
	MACSOLE® rubber sole
	Rugged, self-cleaning sole ridges ensures maximum
	grip for demanding applications on uneven or dirty
	floors (SRC labelling).
	 withstands brief exposure to heat of approx. +300°C
	·
Certificates	Certified with uvex medicare for individual,
	orthopaedic inlay soles and individual adjustments of
	the sole unit such as overall increase, inside and
	outside increase and other solutions.
Areas of application	Medium applications
Technical data	Artno. 6530 3
	Width 12
	Standard EN ISO 20345:2011 S3 HI HRO SRC
	Size 35 – 52
Accessories	uvex 1/2 comfortable climatic insole
Accessories	(article no.: 9534.7-9 + .0)
	,
	Provides the foot with exceptional, full-surface shock
	absorption and ensures comfort in high-strain zones
	Ultra-breathable and moisture-absorbing materials
	Shock absorption zones that assist natural movement Non irritating comfortable surface structure
	Non-irritating, comfortable surface structure
	Laces
	Black (article no.: 9599.9 11)
	Elastic laces (article no.: 9591.100)

Rev. St. 1 Datum: 12.05.2014 Seite 2 von 2