

24.11.2023 SBU-F-PGM-PM

## Product data sheet uvex 2 MACSOLE BOA 65363 S3L FO CI HI HRO SC SR



## UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth

General features	<ul> <li>Sporty and multifunctional S3L winter safety boot</li> <li>Light and flexible</li> <li>Water-repellent, full-grain smooth leather</li> <li>Injection-moulded polyurethane scuffcap to protect upper material on toe cap and significantly extend resistance time</li> <li>BOA® Fit System for a fast, effortless, precision fit</li> </ul>
Protection features	<ul> <li>100% metal-free uvex xenova® toe cap. Compact design, anatomical shape, good lateral stability, no thermal conductivity properties</li> <li>Metal-free, penetration-resistance insole in accordance with the latest standard, which does not impact shoe flexibility</li> <li>Meets ESD requirements: resistance to ground &lt; 35 megaohm</li> </ul>
Comfort features	<ul> <li>Outstanding wearer comfort results from a newly developed last and climate-optimized, breathable materials</li> <li>Virtually seamless design to eliminate pressure points</li> <li>Removable comfort insole, antistatic, with moisture control system and additional shock absorption in the heel and at the front of the foot</li> <li>Soft padded collar and tongue</li> <li>Warm winter lining</li> </ul>
Outsole	<ul> <li>Multilayer shock absorption system comprising PU mid sole, highly slip resistant MACSOLE® rubber outsole and comfortable insole, shock absorption in the front and heel: all this protects</li> </ul>

Rev. St. 1 Seite 1 von 2 Datum: 12.05.2014

	the musculoskeletal system, even over long periods of time
	<ul> <li>Lightweight two-layer insole with excellent shock absorption</li> </ul>
	characteristics and outstanding slip resistance
	<ul> <li>Increased low-temperature flexibility of MACSOLE® rubber sole</li> </ul>
	<ul> <li>Optimized tread design to ensure safety when working on ladders</li> </ul>
	<ul> <li>Rugged, self-cleaning sole ridges ensures maximum grip for</li> </ul>
	demanding applications on uneven or dirty floors (SRC labelling).
	<ul> <li>withstands brief exposure to heat of approx. +300°C</li> </ul>
Certificates	Certified with uvex medicare for individual, orthopaedic inlay soles
Areas of application	Medium applications
Technical data	Artno. 65363
	Width 12
	Standard EN ISO 20345:2022 S3L FO CI HI HRO SC SR
	Size 35 – 52
Accessories	uvex 1/2 comfortable climatic insole
	(article no.: 95349)
	Provides the foot with exceptional, full-surface shock
	absorption and ensures comfort in high-strain zones
	Ultra-breathable and moisture-absorbing materials     Charles have the transition and the transition an
	<ul> <li>Shock absorption zones that assist natural movement</li> <li>Non-irritating, comfortable surface structure</li> </ul>
i	- MODERNIATIO COMPONADIO CHITACO CITUCINO

Rev. St. 1 Datum: 12.05.2014 Seite 2 von 2