

Product data sheet uvex 1 x-craft 6802 1-4 S1 PL FO SR SC



UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth

General features	• Safety class: S1 PL • Shoe type: perforated shoe • Form: A • All sole materials are free of silicone, plasticizers and other substances that interfere with wetting agents: yes • Metal free: no
Protection features	• Upper material: Microfiber • Lining: Distance-Mesh • Anti penetration: textile, 4,5mm nail (L) • Toe cap: xenova composite • Scuff cap: injected with PU midsole (SC) • ESD certification: yes
Comfort features	• Women's last: yes, for sizes 35-40 • Fastening mechanism: Elastic laces for quick release • Removable anti-static comfortable insole with a moisture transport system and additional shock absorption around the heel and forefoot • clima zone clima management
Outsole	• Sole: double-layer

	○ Outsole: PU ○ Ergonomic outsole design bionom x ○ Midsole: uvex i-PUREnrj planet PU ○ Midsole: functional flex groove flex zone ● Resistant to oil and petrol (FO): yes ● Heat insulating (HI): no ● Heat resistant (HRO): no ● Cold resistant (CI): no																				
Certificates	● Orthopedic insole uvex medicare: yes ● Orthopedic adjustment of outsole uvex medicare +: yes ● ESD certification EN 61340-4-3 + EN 61340-5-1: yes																				
Areas of application	● light application																				
Technical data	uvex 1 x-craft perforated shoe S1PL FO SR SC <table><tr><td>Art.-no.</td><td>6802 1</td><td>2</td><td>3</td><td>4</td></tr><tr><td>Width</td><td>10</td><td>11</td><td>12</td><td>14</td></tr><tr><td>Size</td><td colspan="4">35-52</td></tr><tr><td>Standard</td><td colspan="4">EN ISO 20345:2022 S1 PL FO SR SC</td></tr></table>	Art.-no.	6802 1	2	3	4	Width	10	11	12	14	Size	35-52				Standard	EN ISO 20345:2022 S1 PL FO SR SC			
Art.-no.	6802 1	2	3	4																	
Width	10	11	12	14																	
Size	35-52																				
Standard	EN ISO 20345:2022 S1 PL FO SR SC																				
Accessoires	● Exchangeable <i>uvex 1 x-craft clima comfort insole</i> (article-nr.: 9579 7-0)																				