

Product Datasheet uvex 1 G2 68527 - 68529 S1 SRC



UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth

General features	<ul style="list-style-type: none"> • ultra-lightweight S1 safety shoe • made from synthetic materials, making it suitable for people allergic to chrome • all sole materials are free of silicone, plasticisers and other paint wetting impairment substances • individually adjustable elastic laces for quick release
Protection features	<ul style="list-style-type: none"> • new, innovative uvex i-PUREnrj sole technology with the highest level of shock-absorbing properties at the forefoot and at the heel, excellent rebound over the entire midsole and optimal stability thanks to the foam heel basket • meets the ESD specification with volume resistance under 35 megaohms • new wider 100% metal-free uvex xenova® safety toe cap for more toe room and optimum fit – compact design, anatomical shape, good lateral stability and no thermal conductivity • TPU scuffcap to protect against abrasion
Comfort features	<ul style="list-style-type: none"> • outstanding wearer comfort thanks to a newly developed last and climate-optimized, breathable materials • virtually seam-free construction made from extremely breathable and hydrophobic uvex x-dry knit fabric to eliminate pressure points • removable antistatic comfortable insole with a moisture transport system, additional shock absorption around the heel and forefoot and excellent support for the arch

	<ul style="list-style-type: none">• soft padding on the dust tongue and collar• sizes 35 to 40 have been produced using a women's last																
Outsole	<ul style="list-style-type: none">• very slip resistant thanks to polyurethane outsole• excellent cushioning and extremely flexible• self-cleaning tread• resistant to oil and petrol• resistant to temperatures for short periods up to +120°C																
Certificates	<ul style="list-style-type: none">• Certified with uvex medicare+ for individual, orthopedic inlay soles and individual adjustments of the sole unit such as overall increase, inside and outside increase and other solutions.																
Areas of application	<ul style="list-style-type: none">• light applications																
Technical data	<p>uvex 1 G2 safety shoe S1 SRC</p> <table><tr><td>Art.-no.</td><td>68527</td><td>68528</td><td>68529</td></tr><tr><td>Width</td><td>10</td><td>11</td><td>12</td></tr><tr><td>Standard</td><td colspan="3">EN ISO 20345:2011 S1 SRC</td></tr><tr><td>Size</td><td colspan="3">35 – 52</td></tr></table>	Art.-no.	68527	68528	68529	Width	10	11	12	Standard	EN ISO 20345:2011 S1 SRC			Size	35 – 52		
Art.-no.	68527	68528	68529														
Width	10	11	12														
Standard	EN ISO 20345:2011 S1 SRC																
Size	35 – 52																
Accessories	<p><i>Removable uvex 1 G2 comfortable climatic insole</i> (article no.: 94907 - 94909)</p> <ul style="list-style-type: none">• improved full-surface shock absorption• ultra-breathable, moisture-absorbing and quick-drying materials• shock absorption zones support natural movement of the foot• non-irritating, comfortable surface structure• anti-static properties• arch support <p><i>Laces</i></p> <ul style="list-style-type: none">• black (Art.-no.: 9599.9 09)• elastic laces (Art.-no.: 9591.200)																