

uvex

SAFETY FOOTWEAR

02.11.2023
SBU-F-PGM-MA

Product data sheet uvex 3 6873 1-3 S3 FO CI SC SR



UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth

General features	• Protection class: S3 • Footwear type: lace-up boot • Design: B • Are all sole materials are free of silicone, plasticisers and other substances that interfere with wetting agents: yes • Metal free: no
Protection features	• Upper material: uvex waterstop leather • Lining: Textile • Anti penetration: steel • Toecap: xenova composite • Scuff cap: injected with PU midsole (SC) • ESD certification: yes • Extras: uvex anklepro foam
Comfort features	• Women's last option: yes, for sizes 35-40 • Fastening mechanism: uvex lacelock • Removable anti-static comfortable insole with a moisture transport system and additional shock absorption around the heel and forefoot • uvex climazone climatic management • Extras: uvex bionom x design

Outsole	• Sole: double-layer ○ Outsole: PU ○ Midsole: uvex i-PUREnrj PU • Resistant to oil and petrol (FO): yes • Heat insulating (HI): no • Heat resistant (HRO): no • Cold resistant (CI): yes																				
Certificates	• Orthopedic insole uvex medicare: yes • Orthopedic adjustment of outsole uvex medicare +: yes • ESD certification EN 61340-4-3 + EN 61340-5-1: yes																				
Areas of application	• Heavy application																				
Technical data	uvex 3 lace-up boot S3 FO CI SC SR <table><tr><td>Art.-no.</td><td>6873</td><td>1</td><td>2</td><td>3</td></tr><tr><td>Width</td><td></td><td>10</td><td>11</td><td>12</td></tr><tr><td>Size</td><td>36-52</td><td></td><td></td><td></td></tr><tr><td>Standard</td><td>EN ISO 20345:2022</td><td>S3</td><td>FO</td><td>CI SC SR</td></tr></table>	Art.-no.	6873	1	2	3	Width		10	11	12	Size	36-52				Standard	EN ISO 20345:2022	S3	FO	CI SC SR
Art.-no.	6873	1	2	3																	
Width		10	11	12																	
Size	36-52																				
Standard	EN ISO 20345:2022	S3	FO	CI SC SR																	
Accessoires	<i>Removable uvex 3 climatic insole</i> (Article-No.: 8693 7-9)																				