

**Product data sheet**  
**Model 9916000 uvex pronamic visor UV protection filter**



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,  
D-90766 Fürth**

**Product characteristics**

- Polycarbonate visor with uvex supravision excellence coating technology
- Unique click & pull system for easy removal of the visor in click-in positions 3 and 4
- Visor can be pushed over the helmet shell into a parking position
- Well-balanced system, ergonomic relief for the wearer
- Labelled according to application area 3 (liquids) and 9 (molten metal and hot solids)
- Can be combined with uvex pronamic industrial safety helmet B-WR, uvex pronamic B-S-WR, uvex pronamic S-KR, uvex pronamic alpine safety helmet

|                                               |                                                                                                              |
|-----------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| <b>Technical details</b>                      |                                                                                                              |
| <b>Carrier body</b>                           |                                                                                                              |
| Arm material                                  | PA 6                                                                                                         |
| Adapter material                              | PC ABS                                                                                                       |
| Pull button material                          | PA 6                                                                                                         |
| Spring disc material                          | PC ABS                                                                                                       |
| Locking pin material                          | PC PBT                                                                                                       |
| Colour arms and adapter                       | black                                                                                                        |
| Colour pull button                            | grey                                                                                                         |
| <b>Labelling carrier body</b>                 |                                                                                                              |
| Manufacturer                                  | W                                                                                                            |
| EN standard                                   | 166                                                                                                          |
| Area of application                           | 3 (liquid droplets and splashes)<br>8-2 (arc fault according to GS-ET 29)<br>9 (hot solids and molten metal) |
| Mech. Strength                                | B (120 m/s)                                                                                                  |
| Mark of conformity                            | CE                                                                                                           |
| Certification body                            | 0196                                                                                                         |
| <b>Visor</b>                                  |                                                                                                              |
| material                                      | PC                                                                                                           |
| Thickness                                     | 2.2 mm                                                                                                       |
| Coating                                       | uvex supravision excellence                                                                                  |
| colour                                        | colourless                                                                                                   |
| UV protection                                 | UV 400                                                                                                       |
| <b>Lens labelling</b>                         |                                                                                                              |
| filter                                        | 2C-1.2 (EN 170)                                                                                              |
| manufacturer                                  | W                                                                                                            |
| Optical quality class                         | 1                                                                                                            |
| Mechanical strength                           | B (120 m/s)                                                                                                  |
| Field of application                          | 9 (hot solids and molten metal)                                                                              |
| Surface resistance<br>against small particles | K                                                                                                            |
| Resistance to<br>Fogging                      | N                                                                                                            |
| Mark of conformity                            | CE                                                                                                           |

|                      |                                                          |
|----------------------|----------------------------------------------------------|
| <b>Miscellaneous</b> |                                                          |
| Weight               | 196 g                                                    |
| Packaging            | Individually packed in polybag<br>24 pcs in outer carton |
| Standard fulfilment  | EN 166 + EN 170                                          |
| PPE category         | Category II                                              |

### **Spare parts and accessories:**

|                  |                                    |
|------------------|------------------------------------|
| Art.-Nr. 9906013 | Replacement visor lens             |
| Art.-Nr. 9790074 | Sun/rain shield for visor          |
| Art.-Nr. 9954362 | Fabric bag for storing visors      |
| Art.-Nr. 2600236 | uvex pronamic adapter pull-bayonet |