

Product data sheet
Model 9916001 uvex pronamic visor with chin guard



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

Product characteristics

- Polycarbonate visor with uvex supravision excellence coating technology
- Short chin section for additional protection
- Unique click & pull system for easy removal of the visor in click-in positions 3 and 4
- Visor can be pushed over the helmet shell into a parking position
- Well-balanced system, ergonomic relief for the wearer
- Labelled according to application area 3 (liquids) and 9 (molten metal and hot solids)
- Can be combined with uvex pronamic industrial safety helmet B-WR, uvex pronamic B-S-WR, uvex pronamic S-KR, uvex pronamic alpine safety helmet

Technical Details	
Carrier body	
Arm material	PA 6
Adapter material	PC ABS
Pull button material	PA 6
Spring disc material	PC ABS
Locking pin material	PC PBT
Colour arms and adapter	black
Colour pull button	grey
Manufacturer	Labelling carrier body
EN standard	W
Area of application	166
	3 (liquid droplets and splashes)
	8-2 (arc fault according to GS-ET 29)
	9 (hot solids and molten metal)
Mech. Strength	B (120 m/s)
Mark of Conformity	CE
Certification body	0196
Visor	
Material	PC
Thickness	2.2 mm
Coating visor	uvex supravision excellence
Beschichtung chinguard	uncoated
colour	colourless
UV protection	UV 400
Filter	Visor labelling
manufacturer	2C-1.2 (EN 170)
Optical quality class	W
Mech. Strength	1
Area of application	B (120 m/s)
Surface resistance-	9 (hot solids and molten metal)
to small particles	K
Resistance to fogging	N
Mark of conformity	CE

Miscallaneous	
weight packaging	232 g Individually packed in polybag 20 pcs in outer carton
standard fulfilment PPE-category	EN 166 + EN 170 Category II

Spare parts and accessories:

Art.-Nr. 9906014	Replacement visor lens
Art.-Nr. 9790074	Sun/rain shield for visor
Art.-Nr. 9954362	Fabric bag for storing visors
Art.-Nr. 2600236	uvex pronamic adapter pull-bayonet