

Product data sheet
Model 9916 201 uvex pronamic halfvisor
Modell 9916 uvex pronamic halfvisor sun protection filter



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

Produktcharakteristik	• Tinted polycarbonate visor with anti-fog and anti-scratch coating technology • Push button for easy removal of the visor • Visor can be removed from the helmet at any time using the push button • Can be combined with uvex pronamic B-S-WR, uvex pronamic S-KR and uvex pronamic alpine safety helmet for working at height
Technical details Frame Material Colour Producer EN Norm	POM black W 166

Mech. strength	F (45 m/s)
Mark of conformity	CE
visor	
Material	PC
Thickness	1.9mm in middle and 1.33mm at side
Coating Sichtscheibe	anti-fog and anti-scratch
Colour	colourless
UV protection	UV 400
	Marking of the lens
Filter	5-2,5 (EN 172)
Producer	W
optical class	1
Mech. Strength	F (45 m/s)
Surface resistance to fine particles	K
Resistance to fogging	N
Mark of conformity	CE
Miscellaneous	
weight	76 g
packaging	Individually packed in polybag
	50 pc in a carton
Standards	EN 166 + EN 172
PPE category	category II

Spare parts and accesories:

Art.-Nr. 2600237	uvex pronamic adapter push bayonet for uvex hearing protection earmuffs with bayonet connection
------------------	---