

# EVOGuard®M Forestry Helmet Systems

EVOGuard®M2 Forestry Helmet System / AKE24A-400-800



#### DESCRIPTION

The EVOGuard®M Forestry browguard and helmet systems are innovative solutions to protect the wearer in a multitude of high risk working environments. All EVOGuard® visor components are fully compatible with a range of existing EVO® helmet models.

## OPTIONS

EVOGuard®M3 Forestry Helmet System (AKE24A-500-800) EVOGuard®M3 Forestry Helmet System - with Throat Cover & Sun Cape (AKE24E-200-800)

EVOGuard®M2 Forestry Helmet System (AKE24A-400-800)

#### SAFETY STANDARDS

EN 397 • EN 352-3 • EN 1731 • EN 166



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



### SPECIFICATIONS

Peak

Standard



Lateral Deformation Yes Maximum Temperature



ABS Shell Yes

+50°C



Depth Adjustment **3D Harness** 



Ventilation No



Integrated Eyewear Fitted



Optional 2 point chinstrap (EN397 & EN 812 compliant) Optional



Cup Material ABS

Hygiene Hygiene Kit



Increased Robustness resists a 22mm, 43g steel ball travelling at 5.1 metres per second. This is derived from the practical test which is to drop the ball (as stipulated) from a height of 1.3 metres. S



Visor Length 18cm



**BSI Kitemark** Yes



**JSPCheck** 



Yes

### FEATURES



# **Visor Range**

Two high performance complete forestry systems are available, enabling users to select the perfect visor for their task and price point.



# **Dual Layer Protection**

The EVOGuard®M Forestry Helmet and Forestry Browguard Systems both feature a secondary layer of eye protection in the form of the integrated EVOSpec® polycarbonate retractable eyeshield.



Impact Resistance

Minimum Temperature

50 Joules

Molten Metal

Yes

-40°C

Textile

Yes

Fitted

The second

के

& ∭

٢×

V.L.T

Harness

Wheel Ratchet

**Reflective Option** 

ID card holder

Optional 4 point chinstrap (EN397 Compliant)

Optional

Fitted

SNR

Yes

70%

Material

Recyclable

Product Weight

Yes

805g

31 dB

Adjustable

JSP Dagger

Manufacturer's Trademark

Visible Light Transmittance (VLT)



## **Balanced & Secure**

ABS Frame and Woven Stainless Steel Mesh Visor

Fitted to a browguard or helmet, the selflubricating nylon hinges hold the visor securely in position even during extreme movement, whilst offering balanced, even weight distribution.

## **Product Compatibility**

Designed to maximise compatibility with a broad range of JSP products, such as the Force®8 respirator with PressToCheck™, Springfit™



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.





## Supreme Comfort

Features an easy to use Revolution® wheel ratchet and a 3D-Adjustment harness, which offers 1-2-3 point depth settings for increased adaptability to ensure a perfect, secure fit.



disposable masks and the Sonis® helmet mounted ear defender range.

#### Coverage

EVOGuard® visors provide comprehensive facial coverage without limiting movement or vision.

## LOGO

Front

## RANGE



#### DOWNLOADS

- Image Pack (ZIP)
- doc-evoguard.pdf (PDF)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.