

#### Sizes 35 to 50 Ref. PLAHS3SNR

## **Product Highlights**

- Polyester upper made from recycled PET bottles: lightness, breathability, tear and abrasion resistance.
- Bamboo fiber and recycled polyester lining: antiallergic and anti-microbial, thermoregulatory effect.
- Memory Foam by Lemaitre antibacterial insole with memory foam, recycled, antibacterial, shape memory, energy absorption and dissipation, MSD prevention.
- Outsole injected with recycled polyol from our production waste.
- Timeless sneaker style
- Eco-designed safety shoe made from recycled materials and components > 25% recycled or reused materials (ISO 14021: 2016 standard).
- Protective toe cap: HDFC composite fiber.
- Puncture-resistant midsole: 78% recycled high tenacity composite fabric "0" penetration. PS type (3mm nail).



## **CARBON single-density** antistatic sole

- Developed outsole for industrial and urban floors: good adherence
- Sole tested and certified to the additional requirement of slip resistance as per SR in the new standard 20345:2022
- Large surface support: optimum stability
- Shock absorption: preservation of the back and joints.
- Notches for enhanced grip
- Flexibility and lightness: sole that facilitates walking



- Service company, crafts, management
- Logistics, services, handling, distribution, transport
- Public authorities and administrations





## lemaitre-securite.com

Data sheet subject to change, non-contractual photos.

# PLANET HAUT NOIR S3S

New standard 2022: Standard EN ISO 20345:2022

#### **Characteristics of the upper**

- Upper material: water-repellent velvet effect microfiber and 90% recycled PET fabric
- **Tongue:** water-repellent microfiber and 90% recycled PET fabric
- Lining: 61% recycled materials (bambou & recycled polyester)
- Laces: 100% recycled

#### **Charactericts of the sole**

- Designation: CARBON PU2D
- Material: polyurethane with recycled polyol
- Antistatic sole
- Adhesion coefficient (fundamental requirements): forward flat slip: 0,43 (standard ≥ 0,31) forward heel slip: 0,61 (standard ≥ 0,36)
- SR Adhesion coefficient: forward flat slip: 0,27 (standard ≥ 0,19) forward heel slip: 0,48 (standard ≥ 0,22)

VARIANT



#### **Practical information**

Weight of one shoe size 42 : 487 g AET n° 0075/007/161/02/23/0176 EXT 04/05/23

#### Packaging

Size 35 to 42		Size 43 to 50			
<b>shoebox</b> 315 x 220 x 123 mm		shoel	<b>50x</b> 355 x 220 x 130 mm		
carto	<b>n</b> 635 x 445 x 315 mm	carto	<b>n</b> 660 x 450 x 360 mm		
10 sh	oeboxes per carton	10 shoeboxes per carton			
Gencods					
35	3237154523353	43	3237154523438		
36	3237154523360	44	3237154523445		
37	3237154523377	45	3237154523452		
38	3237154523384	46	3237154523469		
39	3237154523391	47	3237154523476		
40	3237154523407	48	3237154523483		
41	3237154523414	49	3237154523490		
42	3237154523421	50	3237154523506		

#### Memo for basic and additional requirements of the standard EN ISO 20345:2022

Safety Footwear	Anti-static shoes	Ci Insulation against cold
S3S 🛃 🐴 🗛 🖻 😡	E Shock absorption at	Hi Insulation against heat
Sliding test	Foe Fuel oil-resistant outsole	Outsole resistance to hot contact
No. Fundamental requirements marking Slip-resistant shoe on a tiled floor with a solution of sodium lauryl sulfate (NaLS).	Wpa Water penetration and water absorption resistant upper	Wr Water resistant
Shoe resistant to slipping on a tiled floor with glycerin.	Abrasion resistant scuff cap	Ladder grip system
	Electrostatic discharge	Ankle protection
200 J toe cap: Protection of the forefoot against		Ū
Non-metallic puncture-resistant midsole resistant with a 3 mm point (type PS)		4

Lemaitre Sécurité 17 rue de Bitschhoffen - CS 90024 F - 67350 Val de Moder Tél. +33 (0)3 88 72 28 80 LEMAITRE Safety since 1974

#### **DON\_LS04TDS0124** update: 02/05/23

Member of



lemaitre-securite.com

SINAMAP

AP