

## BOLIVAR

### 131BB-06 S3S SC FO LG SR

STANDARD EN ISO 20345:2022+A1:2024

SIZES 37-47

Unlined for highest breathability

Dual density **ICON PU/PU** sole designed to offer maximum comfort, slip resistance, excellent performances across all terrains, from wet to dry conditions. It has been tested in SATRA laboratories to resist slipping on metal grates (Kennedy Grating Test) and wooden boards (Scaffold Board Test)



#### Dual density ICON PU/PU

- Resistant to hydrocarbons
- Antistatic sole (A)
- Non-slip sole suitable for use on metal and wooden grates - SATRA Tests
- Self-cleaning profile to ensure maximum ground grip
- Wide fit for maximum stability and protection
- Shock-absorbing heel

**PZX** fiberglass toe cap and **TXZERO STRONG** anti puncture insole made of high tenacity fibers to obtain a flexible textile that adapts to the movement of the foot; it is intrinsically antistatic



The tunnel loops guarantee a quick and easy fit

**IDROTECH** fullgrain leather upper, resistant to water penetration and absorption



Esolight 1.0 polyurethane midsole. The low-density polyurethane microcells enhance energy absorption ensuring comfort and lightness



#### T-01

- Anatomical insole for increased comfort
- High-density foam = energy absorption and rebound
- Lining made from conductive micro-perforated fabric to reduce wear and tear